

Test Doubles





Dario Campagna

What's a Test Double?

Any kind of pretend object that is used in place of a real object for testing purposes.

- Name coined by Gerard Meszaros.
- Comes from the notion of Stunt Doubles in movies.



Bobby Holland Hanton and Chris Hemsworth. Instagram/@bobbydazzler84




Tests in TDD

Should be fast, isolated, specific, deterministic.

Shouldn't depend on data or other fixtures outside the control of each test case.

- File system
- Databases
- Network communications
- Hardware systems
- •






Types of test double

Meszaros defined five particular kinds of double.

- Dummy
- Fake (<u>example</u>)
- Stubs (<u>example</u>)
- Spies
- Mocks






What about concurrency?



Separate the functional and synchronization concerns


Separate the logic that splits a request into multiple tasks from the technical details of how those tasks are executed concurrently.

- We can test-drive the functional behavior in isolation.
- We can test-drive the synchronization via stress-tests.
- We can use end-to-end tests to check that unit-level synchronization policies integrate across the entire system.
- Static analysis can catch further errors.






Example from "Growing Object Oriented Software"





Example from "Growing Object Oriented Software"







References



Mocks Aren't Stubs

https://martinfowler.com/articles/ mocksArentStubs.html

Growing Object Oriented Software

Steve Freeman and Nat Pryce

http://www.growing-object-oriented-software.com