

TECNICHE DI RAPPRESENTAZIONE E MODELLIZZAZIONE DEI DATI

– Part 1 –

(2 CFU out of 6 total CFU)

Link moodle: <https://moodle2.units.it/course/view.php?id=11703>

Teams code: 0ftoqj8

Shell scripting

Exercises.

Exercise 1

Create a new directory, move into it and run the command

```
touch file{1..20}{.{dat,png,txt},\ backup.dat,_bkp.png}
```

- a. — Understand what happened using ls.
- b. — List only files with the .dat extension.
- c. — List only files with number 13 in the name.
- d. — List only backup files.
- e. — List only files containing a space in the name.
- f. — List files with a number that is multiple of 5 before the dot.

Write a bash script which performs all the tasks above, and execute it.

Make the script write the commands and the output of the commands on a file.

Make the script available as a command.

Shell scripting

Exercises.

Exercise 1

Create a new directory, move into it and run the command

```
touch file{1..20}{.{dat,png,txt},\ backup.dat,_bkp.png}
```

- Understand what happened using ls.
- List only files with the .dat extension.
- List only files with number 13 in the name.
- List only backup files.
- List only files containing a space in the name.
- List files with a number that is multiple of 5 before the dot.

Write a bash script which performs all the tasks above, and execute it.

Make the script write the commands and the output of the commands on a file.

Make the script available as a command.

```
#!/bin/bash

echo 'touch file{1..20}{.{dat,png,txt},\ backup.dat,_bkp.png}'
touch file{1..20}{.{dat,png,txt},\ backup.dat,_bkp.png}

echo 'ls *.dat'
ls *.dat
echo 'ls *13*'
ls *13*
echo 'ls *backup*'
ls *backup*
echo 'ls *\ *'
ls *\ *
echo 'ls *5.*; ls *0.*'
ls *5.*; ls *0.*
```

File Content Search Commands

To look for a pattern in one or more files, use the `grep` series of commands.

The **grep** commands search for a string in the specified files and display the output on standard output.

egrep (the initial e stands for extended) searches for a specified pattern in one or more files. The pattern can be a regular expression to match any single character.

* to match one or more single characters that precede the asterisk.

^ to match the regular expression at the beginning of a line.

\$ to match the regular expression at the end of a line.

+ to match one or more occurrences of a preceding regular expression.

? to match zero or more occurrences of a preceding regular expression.

[] to match any of the characters specified within the brackets.

Shell scripting

File Content Search Command **egrep**

Assume we have a file:

```
(base) milena:test_bash milenavalentini$ cat file_to_grep.txt
-- This is a test file
Lorem ipsum dolor sit amet,
consectetur adipiscing elit, sed do eiusmod tempor incididunt
ut labore et dolore magna aliqua. Ut enim ad minim veniam,
quis nostrud exercitation ullamco laboris nisi
ut aliquip ex ea commodo consequat.
Duis aute irure dolor in reprehenderit in voluptate velit esse
cillum dolore eu fugiat nulla pariatur.
Excepteur sint occaecat cupidatat non proident,
sunt in culpa qui officia deserunt mollit anim id est laborum.

---- This was a TEST FILE
```

Shell scripting

File Content Search Command **egrep**

```
[(base) milena:test_bash milenavalentini$ cat file_to_grep.txt
-- This is a test file
Lorem ipsum dolor sit amet,
consectetur adipiscing elit, sed do eiusmod tempor incididunt
ut labore et dolore magna aliqua. Ut enim ad minim veniam,
quis nostrud exercitation ullamco laboris nisi
ut aliquip ex ea commodo consequat.
Duis aute irure dolor in reprehenderit in voluptate velit esse
cillum dolore eu fugiat nulla pariatur.
Excepteur sint occaecat cupidatat non proident,
sunt in culpa qui officia deserunt mollit anim id est laborum.

---- This was a TEST FILE
```

To find all occurrences of **file**, use:

```
[(base) milena:test_bash milenavalentini$ egrep file file_to_grep.txt
-- This is a test file
[(base) milena:test_bash milenavalentini$ egrep FILE file_to_grep.txt
---- This was a TEST FILE
[(base) milena:test_bash milenavalentini$ egrep -i file file_to_grep.txt
-- This is a test file
---- This was a TEST FILE
```

(flag **-i** for case insensitivity)

Shell scripting

File Content Search Command **egrep**

```
[(base) milena:test_bash milenavalentini$ cat file_to_grep.txt
-- This is a test file
Lorem ipsum dolor sit amet,
consectetur adipiscing elit, sed do eiusmod tempor incididunt
ut labore et dolore magna aliqua. Ut enim ad minim veniam,
quis nostrud exercitation ullamco laboris nisi
ut aliquip ex ea commodo consequat.
Duis aute irure dolor in reprehenderit in voluptate velit esse
cillum dolore eu fugiat nulla pariatur.
Excepteur sint occaecat cupidatat non proident,
sunt in culpa qui officia deserunt mollit anim id est laborum.

---- This was a TEST FILE
```

To display the relative line number of the line containing the searched pattern, use the **-n** flag:

```
[(base) milena:test_bash milenavalentini$ egrep -i -n file file_to_grep.txt
1:-- This is a test file
12:---- This was a TEST FILE
[(base) milena:test_bash milenavalentini$ egrep -n ut file_to_grep.txt
4:ut labore et dolore magna aliqua. Ut enim ad minim veniam,
6:ut aliquip ex ea commodo consequat.
7:Duis aute irure dolor in reprehenderit in voluptate velit esse
```

Shell scripting

File Content Search Command **egrep**

```
[(base) milena:test_bash milenavalentini$ cat file_to_grep.txt
-- This is a test file
Lorem ipsum dolor sit amet,
consectetur adipiscing elit, sed do eiusmod tempor incididunt
ut labore et dolore magna aliqua. Ut enim ad minim veniam,
quis nostrud exercitation ullamco laboris nisi
ut aliquip ex ea commodo consequat.
Duis aute irure dolor in reprehenderit in voluptate velit esse
cillum dolore eu fugiat nulla pariatur.
Excepteur sint occaecat cupidatat non proident,
sunt in culpa qui officia deserunt mollit anim id est laborum.

---- This was a TEST FILE
```

To search for a pattern as a word, use the **-w** flag:

```
[(base) milena:test_bash milenavalentini$ egrep -w in file_to_grep.txt
Duis aute irure dolor in reprehenderit in voluptate velit esse
sunt in culpa qui officia deserunt mollit anim id est laborum.
```

Shell scripting

File Content Search Command **egrep**

```
(base) milena:test_bash milenavalentini$ cat file_to_grep.txt
-- This is a test file
Lorem ipsum dolor sit amet,
consectetur adipiscing elit, sed do eiusmod tempor incididunt
ut labore et dolore magna aliqua. Ut enim ad minim veniam,
quis nostrud exercitation ullamco laboris nisi
ut aliquip ex ea commodo consequat.
Duis aute irure dolor in reprehenderit in voluptate velit esse
cillum dolore eu fugiat nulla pariatur.
Excepteur sint occaecat cupidatat non proident,
sunt in culpa qui officia deserunt mollit anim id est laborum.

---- This was a TEST FILE
```

To find the total number of lines in which the specified pattern occurs, use the **-c** flag:

```
(base) milena:test_bash milenavalentini$ egrep -i -c test file_to_grep.txt
2
```

Shell scripting

File Content Search Command **egrep**

```
[(base) milena:test_bash milenavalentini$ cat file_to_grep.txt
-- This is a test file
Lorem ipsum dolor sit amet,
consectetur adipiscing elit, sed do eiusmod tempor incididunt
ut labore et dolore magna aliqua. Ut enim ad minim veniam,
quis nostrud exercitation ullamco laboris nisi
ut aliquip ex ea commodo consequat.
Duis aute irure dolor in reprehenderit in voluptate velit esse
cillum dolore eu fugiat nulla pariatur.
Excepteur sint occaecat cupidatat non proident,
sunt in culpa qui officia deserunt mollit anim id est laborum.

---- This was a TEST FILE
```

To get a list of all the lines that do not contain the specified pattern, use the **-v** flag:

```
$ egrep -i -v test file_to_grep.txt
```

```
[(base) milena:test_bash milenavalentini$ egrep -i -v test file_to_grep.txt
Lorem ipsum dolor sit amet,
consectetur adipiscing elit, sed do eiusmod tempor incididunt
ut labore et dolore magna aliqua. Ut enim ad minim veniam,
quis nostrud exercitation ullamco laboris nisi
ut aliquip ex ea commodo consequat.
Duis aute irure dolor in reprehenderit in voluptate velit esse
cillum dolore eu fugiat nulla pariatur.
Excepteur sint occaecat cupidatat non proident,
sunt in culpa qui officia deserunt mollit anim id est laborum.
```

Shell scripting

Exercise with the command **egrep**

Create a file and write (copy and paste is OK) in it several lines of text, making sure to go often to new line. Repeat some lines more than once.

Become familiar with the following commands:

egrep *flags* pattern_being_searched file_where_to_search

with the following flags: **-i -n -v -w -c**

and with some combinations of the flags above.

Shell scripting

Variables. They are parameters with a name.

They are created and updated by the user, and available in the environment.

They are untyped.

The variable name is called identifier: it's a word consisting only of letters, digits and underscores and beginning with a letter or an underscore.

Shell scripting

Variables. They are parameters with a name.

They are created and updated by the user, and available in the environment.

They are untyped.

No need to declare a variable, just assigning a value to its reference will create it.

```
(base) milena:test_bash milenavalentini$ STR="Hello World"
(base) milena:test_bash milenavalentini$ echo $STR
Hello World
(base) milena:test_bash milenavalentini$ a=5324; printf $a\\n
5324
```

variableName=variableContent

If not existing, the global variable **variableName** is created, and the content **variableContent** is put into it

If existing, the content of **variableName** is set to **variableContent**

If **variableName** exists and it is read-only, an error occurs.

Shell scripting

Variables. They are parameters with a name.

They are created and updated by the user, and available in the environment.

They are untyped.

No need to declare a variable, just assigning a value to its reference will create it.

variableName=variableContent

If not existing, the global variable **variableName** is created, and the content **variableContent** is put into it

If existing, the content of **variableName** is set to **variableContent**

If **variableName** exists and it is read-only, an error occurs.

```
(base) milena:test_bash milenavalentini$ variableName=variableContent
(base) milena:test_bash milenavalentini$ variableName = variableContent
-bash: variableName: command not found
```

Bash arithmetic expansion

Arithmetic expansion provides a powerful tool to perform (integer) arithmetic operation.

Translating a string into a numerical expression can be done using:

\$ (...)

double parentheses, or

let

Bash arithmetic expansion

Arithmetic expansion provides a powerful tool to perform (integer) arithmetic operation.

Translating a string into a numerical expression can be done using:

\$ (...)

double parentheses, or

let

example:

```
[(base) milena:test_bash milenavalentini$ z=15
[(base) milena:test_bash milenavalentini$ z=$(expr $z + 3)
[(base) milena:test_bash milenavalentini$ echo $z
18
```

arithmetic operators:

```
[(base) milena:test_bash milenavalentini$ a=$(expr 5 + 3)
[(base) milena:test_bash milenavalentini$ echo "5 + 3 = $a"
5 + 3 = 8
```

Bash arithmetic expansion

Arithmetic expansion provides a powerful tool to perform (integer) arithmetic operation.

Translating a string into a numerical expression can be done using:

\$ (...)

double parentheses, or

let

incrementing a variable:

```
[(base) milena:test_bash milenavalentini$ a=5  
[(base) milena:test_bash milenavalentini$ a=$(expr $a + 1)  
[(base) milena:test_bash milenavalentini$ echo "a + 1 = $a"  
a + 1 = 6
```

modulo (i.e. remainder of a division):

```
[(base) milena:test_bash milenavalentini$ b=$(expr 5 % 3)  
[(base) milena:test_bash milenavalentini$ echo "5 mod 3 = $b"  
5 mod 3 = 2
```

Bash arithmetic expansion

Arithmetic expansion provides a powerful tool to perform (integer) arithmetic operation.

Translating a string into a numerical expression can be done using:

\$ (...)

double parentheses, or

let

logical operators (return 1 if true):

```
[(base) milena:test_bash milenavalentini$ x=10
[(base) milena:test_bash milenavalentini$ y=11
[(base) milena:test_bash milenavalentini$ b=$(expr $x = $y)
[(base) milena:test_bash milenavalentini$ echo "b = $b"
b = 0
```

verifies

it's false!

Bash arithmetic expansion

Arithmetic expansion provides a powerful tool to perform (integer) arithmetic operation.

Translating a string into a numerical expression can be done using:

\$ (...)

double parentheses or

let

arithmetic expansion:

```
[ (base) milena:test_bash milenavalentini$ n=0
[ (base) milena:test_bash milenavalentini$ echo "n = $n"
n = 0
[ (base) milena:test_bash milenavalentini$ (( n += 1 ))
[ (base) milena:test_bash milenavalentini$ echo "n = $n"
n = 1
```

Bash arithmetic expansion

Arithmetic expansion provides a powerful tool to perform (integer) arithmetic operation.

Translating a string into a numerical expression can be done using:

\$ (...)

double parentheses, or

let

The **let** operator actually performs arithmetic evaluation, rather than expansion.

```
[(base) milena:test_bash milenavalentini$ z=1
[(base) milena:test_bash milenavalentini$ let z=z+5
[(base) milena:test_bash milenavalentini$ echo $z
6
[(base) milena:test_bash milenavalentini$ let "z += 5"
[(base) milena:test_bash milenavalentini$ echo $z
11
```

Double quotes allow you using spaces in variable assignment!

Exercise: try to translate examples done with `expr` and double parentheses by using `let`.

Redirection with pipe

Pipe `|` is a special character.

It passes the output (stdout) of a previous command to the input (stdin) of the next one, or to the shell.

It's a method to chain commands together.

Redirection with pipe

Pipe | is a special character.

It passes the output (stdout) of a previous command to the input (stdin) of the next one, or to the shell.

It's a method to chain commands together.

Example:

```
[(base) milena:test_bash milenavalentini$ ls -l file*4*
-rw-r--r--  1 milenavalentini  staff  0 Oct  4 13:42 file14 backup.dat
-rw-r--r--  1 milenavalentini  staff  0 Oct  4 13:42 file14.dat
-rw-r--r--  1 milenavalentini  staff  0 Oct  4 13:42 file14.png
-rw-r--r--  1 milenavalentini  staff  0 Oct  4 13:42 file14.txt
-rw-r--r--  1 milenavalentini  staff  0 Oct  4 13:42 file14_bkp.png
-rw-r--r--  1 milenavalentini  staff  0 Oct  4 13:42 file4 backup.dat
-rw-r--r--  1 milenavalentini  staff  0 Oct  4 13:42 file4.dat
-rw-r--r--  1 milenavalentini  staff  0 Oct  4 13:42 file4.png
-rw-r--r--  1 milenavalentini  staff  0 Oct  4 13:42 file4.txt
-rw-r--r--  1 milenavalentini  staff  0 Oct  4 13:42 file4_bkp.png
[(base) milena:test_bash milenavalentini$ ls -l file*4* | wc -l
  10
[(base) milena:test_bash milenavalentini$ _
```

ls -l # Passes the output of "ls -l" to the wc -l, the second command, which counts files.

Conditional blocks

```
#!/bin/bash
if [ "foo" = "foo" ]; then
  echo expression evaluated as true
else
  echo expression evaluated as false
fi
```

if is a keyword

Example of its syntax

if executes a command (or a set of commands) and checks that command exit code to see whether it was successful or not

command exit code = 0 means success

Conditional blocks

```
#!/bin/bash
if [ "foo" = "foo" ]; then
  echo expression evaluated as true
else
  echo expression evaluated as false
fi
```

```
#!/bin/bash
if [ "foo" = "foo" ]
then
  echo expression evaluated as true
else
  echo expression evaluated as false
fi
```

Different layouts work.

Conditional blocks

```
#!/bin/bash
if [ "foo" = "foo" ]; then
    echo expression evaluated as true
else
    echo expression evaluated as false
fi
```

```
#!/bin/bash
a=2
if [ $a == 3 ]; then
    echo equal to
elif [ $a -gt 3 ]; then
    echo greater than
else
    echo lower than
fi
```

Conditional blocks

Relational operators

- -lt (<)
- -gt (>)
- -le (<=)
- -ge (>=)
- -eq (==)
- -ne (!=)

Main conditional operators

Boolean operators

- && and
- || or
- | not

Files operators:

- if [-x "\$filename"]; then # if filename is executable
- if [-e "\$filename"]; then # if filename exists
-

Conditional loops

while Repeat as long as a command is executed successfully (exit code is 0)

until Repeat as long as a command is executed unsuccessfully (exit code is not 0).
Not that used, while is usually preferred.

for It comes in two versions

- to iterate over an integer index
- to iterate over a list

Conditional loops

The keywords **while** and **until**

```
while COMMAND; do
    # Body of the loop: entered if COMMAND's exit code = 0
done

until COMMAND; do
    # Body of the loop: entered if COMMAND's exit code ≠0
done
```

- Testing command like `[` or `[[` are often used
- Infinite loops can be achieved using the builtins **true**, **false** and `:`
- Use the **continue** builtin to skip ahead to the next iteration of a loop without executing the rest of the body
- Use the **break** builtin to jump out of the loop and continue with the script after it
- Both **continue** and **break** accept an optional integer to act on nested loops

Conditional loops

The keywords **while** and **until**

```
$ until false; do # while true; do # while ;; do
> echo "Infinite loop"
> sleep 3
> done
Infinite loop
Infinite loop
^C # Press CTRL-C
```

```
# An example of countdown...
$ deadline=$(date -d "8 seconds" +%s); \
> now=$(date +%s); \
> while [[ $(date +%s) -gt $deadline ]]; do
> echo "$(date +%s) seconds to BOOM!"
> sleep 3
> now=$(date +%s)
> done; echo 'BOOOOUM!!!'
8 seconds to BOOM!
5 seconds to BOOM!
2 seconds to BOOM!
BOOOOUM!!
```

Conditional loops

The keywords **while** and **until**

```
$ i=0; \  
> while [[ ${i} -lt 5 ]]; do  
>     j=0  
>     while [[ ${j} -le 5 ]]; do  
>         if [[ ${j} -le ${i} ]]; then  
>             printf "${(i+j)} "  
>             j=$((j + 1))  
>         else  
>             printf '\n'  
>             i=$((i + 1))  
>             continue 2  
>         fi  
>     done  
> done  
0  
1 2  
2 3 4  
3 4 5 6  
4 5 6 7 8
```

Conditional loops

The keyword **for**

```
for VARIABLE in WORDS; do
    # Body of the loop: VARIABLE set to WORD
done

for (( EXPR1; EXPR2; EXPR3 )); do # Expressions can be empty
    # Body of the loop
done
```

In the second form:

- it starts by evaluating the first arithmetic expression
- it repeats as long as the second arithmetic expression is successful
- at the end of each loop evaluates the third arithmetic expression

Conditional loops

The keyword **for**

```
$ for (( ; 1; )); do echo "Infinite loop"; sleep 1; done
Infinite loop
Infinite loop
^C      # Press CTRL-C
```

```
$ for index in {0,1}{0,1}; do
>   echo "${index} in base 2 is $(( 2#${index})) in base 10"
> done; unset index
00 in base 2 is 0 in base 10
01 in base 2 is 1 in base 10
10 in base 2 is 2 in base 10
11 in base 2 is 3 in base 10
```

```
# BAD code!
```

```
$ for file in $(ls *.mp3); do   # AAAARGH!
>   rm "$file"
> done; unset file
```

```
$ ls
Happy birthday.mp3  Hello.mp3
$ for file in *.mp3; do   # GOOD code
>   rm "$file"
> done; unset file
```

Conditional loops

continue statement in a for loop

- **continue** stops the execution of the commands in the loop and jumps to the next value in the series.

Pseudo-code example:

```
for i in [series]
do
  command 1
  command 2
  if (condition)           # Condition to jump over command 3
    continue              # skip to the next value in "series"
  fi
  command 3
done
```

continue statement in iteration

- **continue** is used in scripts to skip the current iteration of a loop and continue to the next iteration of the loop.

Conditional loops

break command in iteration

break: used to exit out of the current loop before the actual end of the loop

When used in scripts with **multiple loops**, we use `break 2` if we are in an inner loop and we want to jump out of the outer loop

```
#!/bin/bash
# Breaking outer loop from inner loop
for (( a = 1; a < 5; a++ ))
do
echo "outer loop: $a"
for (( b = 1; b < 100; b++ ))
do
if [ $b -gt 4 ]
then
break 2
fi
echo "Inner loop: $b "
done
done
```

Conditional loops

Examples

Counting:

```
#!/bin/bash
for i in {1..25}
do
    echo $i
done
```

or:

```
#!/bin/bash
for ((i=1;i<=25;i+=1))
do
    echo $i
done
```

Counting on "n" steps

```
#!/bin/bash
for i in {0..25..5}
do
    echo $i
done
```

That will count with 5 to 5 steps.

Counting backwards

```
#!/bin/bash
for i in {25..0..-5}
do
    echo $i
done
```

Acting on files

```
#!/bin/bash
for file in ~/*.txt
do
    echo $file
done
```

That example will just list all files with "txt" extension. It is the same as `ls *.txt`

Calculate prime numbers

```
#!/bin/bash
read -p "How many prime numbers ?:" num
c=0
k=0
n=2

numero=${num-1}
while [ $k -ne $num ]; do
    for i in `seq 1 $n`;do
        r=${n%i}
        if [ $r -eq 0 ]; then
            c=${c+1}
        fi
    done
    if [ $c -eq 2 ]; then
        echo "$i"
        k=${k+1}
    fi
    n=${n+1}
    c=0
done
```

Conditional loops

Exercises

Exercise 1.

Write a bash script which lists all the items in the current directory.

Exercise 2.

Write a bash script which displays all the numbers ranging from 1 to 10.

Exercise 3.

Write a bash script which prints in the standard output the values of the index i , which ranges from 0 to 20 with an increment of 2.

Conditional loops

Exercises

Exercise 1.

Write a bash script which lists all the items in the current directory.

```
#!/bin/bash
for i in $( ls ); do
    echo item: $i
done
```

Exercise 2.

Write a bash script which displays all the numbers ranging from 1 to 10.

```
#!/bin/bash
for i in $(seq 1 10); do
    echo $i
done
```

Exercise 3.

Write a bash script which prints in the standard output the values of the index *i*, which ranges from 0 to 20 with an increment of 2.

```
#!/bin/bash
for (( i = 0 ; i <= 20 ; i += 2 )) ;
do
    echo "i has the values of $i"
done
```

Conditional loops

Exercises

Exercise 4.

Write a bash script which outputs the value of a counter (initially set to 0) as long as it is smaller than 10.

Exercise 5.

Write a bash script which displays the value of an index (set to 20 at the beginning) until it drops below 10.

Conditional loops

Exercises

Exercise 4.

Write a bash script which outputs the value of a counter (initially set to 0) as long as it is smaller than 10.

```
#!/bin/bash
COUNTER=0
while [ $COUNTER -lt 10 ]; do
    echo The counter is $COUNTER
    let COUNTER=COUNTER+1
done
```

Exercise 5.

Write a bash script which displays the value of an index (set to 20 at the beginning) until it drops below 10.

```
#!/bin/bash
COUNTER=20
until [ $COUNTER -lt 10 ]; do
    echo COUNTER $COUNTER
    let COUNTER-=1
done
```

Conditional loops

Read files

```
read -r riga < $file
echo $riga
```

```
#!/bin/bash
while IFS=' ' read -r line || [[ -n "$line" ]];
do
    echo "Text read from file: $line"
done < "$1"
```

```
for word in $(cat $file); do
    echo $line
done
```

Conditional loops

Conditional statements: files and dir

```
If [ -e $file_name]; then  
    echo exists  
fi
```

```
If [ -d $file_name]; then  
    echo is a dir  
fi
```

```
If [ -f $file_name]; then  
    echo exists and is a file  
fi
```

```
If [ !-d $file_name]; then  
    echo is not a dir  
fi
```

Sed

<https://www.gnu.org/software/sed/manual/sed.html>

Sed is a non interactive editor. <https://www.gnu.org/software/sed/manual/sed.html>

It is generally used to parse and transform text, using a simple, compact programming language.

It allows to modify a file using scripts with instructions for sed editing plus the filename.

Example of string substitution:

```
$sed 's/old_text/new_text/g' /tmp/testfile
```

Sed substitute the string 'old_text' with the string 'new_text' reading from file /tmp/testfile.

The result is redirected to stdout, but it can be redirected also to a file using '>'

```
$sed 12, 18d /tmp/testfile
```

Sed displays all the rows from 12 to 18. The original file is not modified by this command, but if you redirect stdout on a new file, it is different from the original one.

Awk

<https://www.gnu.org/software/gawk/manual/gawk.html>

Awk matches a string on the base of a regular expression and execute a required action:

Create a file filetext as follow:

```
cat filetext <
test123
test
Tteesstt
EOF
```

```
$awk '/test/ {print}' /tmp/filetext
test123
test
```

The regular expression requires to match the string 'test'

The required action is to 'print' how many times the string 'test' is found.

```
$awk '/test/ {i=i+1} END {print i}' /tmp/filetext
3
```

Sed, Awk and more

Exercise

Generate two set of files: file1.dat, file2.dat, ..., file20.dat and file1.txt, file2.txt, ..., file20.txt

Write in each of them the following test:

```
test123 test12 test1  
1 2 3 4
```

Create one file by concatenating all the files having the extension “.dat” in a file_TOT.dat

Count in how many lines the string test12 occurs
in the file_TOT.dat and print this number in
the standard output

Write in a file called extracted_file.dat
only the line including words of the file_TOT.dat